

# Simplicity

Is it really too much to ask for?



NLS believes that every product we design, engineer and manufacture should be simple to install and simple to use and should be able to work in various configurations. This is how we came up with the RFT2.....a **1U Slide-out Rackmount 17" LCD and Intel-based keyboard**. No matter what your application, from commercial to military, our products should be simple to use and built to last. One keyboard able to function as USB or PS/2 (without a horrid dongle), one display that can connect to DVI or HD-15, one rackslide that will cover all rack types, and a simple to use, easy to install (taking one person and not three) cable management system combined with all the cables you'll need to connect to your server, makes life.....well, simple.



AutoLocking Rackslides

No bothering with Thumbscrews or special locks. Just close the unit and it self-locks into the rack. To open, grab the handles and open. Simple.



Front USB Port

With the front USB port, getting access to your server is easy. No more fighting to get behind the rack, get the door open and plug in your USB device.



USB - PS/2 Keyboard

USB and PS/2 on the same keyboard... without dongles. Now if your configuration changes, you won't need to worry about your equipment.



HD-15 and DVI Connections

HD-15 and DVI connections are both available so there's no need to worry about what your server or KVM uses.



Cable Select for Keyboard and LCD

Need USB? Need PS/2? Need HD-15? Need DVI? No problem, just plug it in and go! All cables are supplied with every unit.



Integrated Cable Mgt

Cable management has never been easier! This system attaches to the slide rails and not your rack, so you'll never need to worry about depth. Best thing is it takes about 10 seconds to install....and without screws!

## LCD Technology:

### Active matrix TFT color LCD

- . 17.1" diagonal screen size
- . 1280 x 1024 addressable pixels
- . 1280 x 1024 maximum resolution
- . 0.264mm x 0.264mm pixel pitch
- . 260cd/m<sup>2</sup> (typ.) brightness
- . 400:1(typ.) contrast ratio
- . Tr: 25ms / Tf: 16ms (typ.)
- . L/R=80° / 80°, U/D=75° / 75° viewing angle
- . 4 CCFLs backlights lamp with 30,000 hours life (min.)

Display Resolution: 1280 pixels(H) x 1024 lines(V)

Active Display Area: 337.1mm(H) x 270.1mm(V)

Displayable Color: 16.7M colors

### Compatibility

- IBM & VESA

Native 1280 x 1024 @ 60Hz

- Sun Microsystems: 1152 x 900, 66 / 76Hz

### I/O Connectors:

- DC power in
- 90-240v, 50-60Hz
- VGA in D-sub 15 pin
- DVI-I
- PS/2 Keyboard/Mouse
- USB Keyboard/Mouse
- USB 2.0 Front Port

Certs: CSA, CE, CB, RoHS

See more specs on our website [www.NLSdisplays.com](http://www.NLSdisplays.com)

### Key Features:

- Auto-Locking Rackslides
- USB-PS/2 Combo Keyboard/Mouse (cable select)
- 3-Button Trackball
- RGB and DVI video connections
- Front USB Port
- Integrated Cable Management System
- Rackslides fit 24" to 36" rails
- **Includes all cables: video, USB, PS/2, power.**
- 2 Year Parts & Labor Warranty

