



NEURO LOGIC
SYSTEMS

PRODUCTS

CF-19 19" Ruggedized LCD



THE CF PRODUCT LINE CONSISTS OF FLAT-PANEL DISPLAYS ENGINEERED FOR USE IN HARSH, DEMANDING ENVIRONMENTS, INCLUDING SHIPBOARD AND MILITARY. NEURO LOGIC ONLY USES THE HIGHEST QUALITY LCDs AVAILABLE. ALL LCDs AND CONTROLLERS ARE CUSTOM BUILT TO NLS SPECIFICATIONS. THIS DOES NOT MEAN THEY ARE THE MOST EXPENSIVE EITHER! OUR PRODUCTS HAVE BEEN USED IN APPLICATIONS FROM MUSEUMS TO NETWORK ROOMS TO MILITARY VEHICLES TO MILITARY AIRPLANES.



KEY FEATURES

- Resistive, Surface Acoustic Wave (SAW), and Infrared Touchscreen (optional)
- 3mm heat-treated glass (on most models)
- 80-degree (up/down/left/right) viewing on all panels
- Rear-mounted OSD controls
- Backlight/Inverter Controls (optional)
- Fan-cooled electronics (optional)

- HD-15 - BNC or NTSC
- RGB Green Sync, RS-170, Y and C (S-video) thru BNC, NTSC, VGA
- DVI/Digital Video Interface (optional)
- Black powdercoat aluminum enclosure w/ handles
- Based on proven COTS LCD technology for low risk and high quality at an affordable cost
- Superior reliability and


- maintainability over CRTs means a lower life cycle cost
- NEMA 4 front option
- Mil-Spec 461E, 901 and 810 available
- 24 and 48 volt and 400Hz power supply options
- Custom modifications available on all models

CF-19: 19" RUGGEDIZED LCD

CF-19: 19" Ruggedized LCD



PRODUCTS



LCD TECHNOLOGY

LCD Technology:

- Active matrix TFT color LCD
- 19.1" diagonal screen size
- 1280 x 1024 maximum resolution
- 0.294mm x 0.294mm pixel pitch
- 250cd/m² (typ.) brightness
- 700:1 (typ.) contrast ratio
- Tr: 12.8ms / Tf: 5.2ms; 12ms (typ.)
- L/R=80° / 80°, U/D=70° / 70° viewing angle
- 4 CCFLs backlights lamp w/30,000 hrs life

Display Resolution:

1280 pixels(H) x 1024 lines(V)

Active Display Area:

376.1mm(H) x 301.1mm(V)

Displayable Color: 16.7M colors

Compatibility:

IBM & VESA

VESA SXGA 1280 x 1024 60 / 75Hz

Apple Macintosh

1024 x 768 75Hz

SunMicro 1152 x 900, 66 / 76Hz

Input Signal:

- Video: analog RGB 0.7 Vp-p
- Sync: separate sync, composite sync, sync. on green

Auto-adjustment: Yes

I/O Connectors:

- DC power in
- VGA in D-sub 15 pin

Power Consumption:

35 watt (max.), 28W Typ, < 5 watt (off mode)
 90-260VAC @ 50/60Hz

Operating Temperature:

- 0°-50°C / 32°-122°F
- Humidity: 95% maximum

Storage Temperature: -20°-60°C / -4°-140°F

Vibration & Shock: (non-mil test)

Freq: 10-200Hz

Sweep: 30 min (X,Y,Z)

Accel: 1.5G (10-200Hz P-P)

Shock Test Spec: (non-mil test)

Accel: 50G

Active Time: 20

Wave Form: half-sin

Times: 1

Pressure: Max: 1040hPa; 0m=sea level

Min: 674hPa; 3048m=10,000ft

Non-operation Alt = 30k ft, 9145m

MTBF 30,000 hours

Power Supply Options: DC 12/24/48 Volt & 400Hz

Mil Specs: Optional: 461E - 901D - 810

LCD Agency approval: FCC-B, CE-B, VCCI-II,

BSMI, CCIB, UL, CUL, TUV, CB, TCO'99

Unit Certs: CE, CSA, CB, Solaris Ready Approved

www.NLsdisplays.com

Sales and Product : sales@nlsdisplays.com



451-C CONSTITUTION AVE. CAMARILLO, CA 93012

T 1.805.389.5435 | F 1.805.389.5436

NEURO LOGIC SYSTEMS